

Model LSH01

Section 4

Lift Style:

LSH01A

LSH01B

LSH01C

LSH01D



A popular option for general industry use, the LSH01 Hydraulic Scissor Lift Table provides a welded construction top and bottom frame along with many safety features. Available with lift capacities ranging from 500 to 4000 lbs., the LSH01 has several travel options, from 24” to 60.” The rectangular platforms range from 17” to 24” wide and 42” through 88” long.

A reliable lift for general industry applications, the LSH01 utilizes captured wheel tracks on both the platform and the base, which provide strong, stable support for applications that might employ offset loading on occasion.

Standard Features

- **Low profile** accommodates a wide range of worker heights and applications
- **Modular design** is easily customizable to application specifications
- **High-strength steel, welded construction** built to safety factors required by customer application and in compliance with ANSI MH29.1-1994
- **High capacity lifting** up to 57,000 lbs (25,855 kg)
- **Variable duty cycles** from low to high for cost flexibility to fit each application
- **Self-lubricating PTFE overlay** on bearings at all pivot points for high loads and long life
- **Captured wheel guides** to prevent top and bottom lift platforms from tipping
- **Stackable lift modules** for added lift travel
- **Virtually maintenance-free** for low-cost operation and minimal downtime
- **Enamel-based acrylic paint** applied to all surfaces after being cleaned and primed
- **Welded cylinder construction** honed steel, piston rod chromed, ground, and polished
- **NEMA 4X and 13** push button control enclosure for washdown, oil, and corrosion protection
- **Pressure relief valve** to ensure safe line pressure
- **Check valve** for pump protection
- **Maintenance stop** to ensure safe line pressure

Options

- **Portability kits** allows lift system to be moved with ease
- **High speed capability** with a full cycle in under 10 seconds
- **Safety skirting** to protect from pinch points and debris

Continued ↓

Lift Style LSH01B

Section 4.2


Travel 36"



Nomenclature

Product Type: Lift Scissor Hydraulic
 Lift Style: 01B
 Capacity: 40 = 4000 lbs
 Raised Height: 45"
 Platform Size: 24" width × 55" length

Model LSH 01B - 40 - 45 - 2455



Travel in	Model	Capacity lbs	Lowered Height in	Travel in	Raised Height in	Platform Size ⁵		Base Size ⁵ in × in	Number of Cylinders	Ship Weight ¹ lbs
						Width in	Length in			
36	LSH01B-10-45-2455	1000	9	36	45	24 - xx	55 - xx	24 × 55	2	920
36	LSH01B-20-45-2455	2000	9	36	45	24 - xx	55 - xx	24 × 55	2	920
36	LSH01B-30-45-2455	3000	9	36	45	24 - xx	55 - xx	24 × 55	2	920
36	LSH01B-40-45-2455	4000	9	36	45	24 - xx	55 - xx	24 × 55	2	920

Values rounded to the nearest 1"

Notes

- 1 Ship weights are estimated and do not include oversize platforms or options
- 2 Width and length dimensions reference the main structure of the lift system and do not include structures such as floor tabs, bolt heads, etc. See drawing for actual dimensions
- 3 Lifts must be center loaded when at full capacity
- 4 Side and end load capacities are derated 2% per inch of increase top plate size from base size

Continued ↓

Lift Style LSH01B

Section 4.2


Travel 36"



Nomenclature

Product Type: Lift Scissor Hydraulic
 Lift Style: 01B
 Capacity: 40 = 4000 lbs
 Raised Height: 45"
 Platform Size: 24" width x 55" length

Model LSH 01B - 40 - 45 - 2455



Lift Standard Specifications:

- 1 Hydraulic Power Unit: Externally Mounted
 - Up: Power
 - Down: Gravity
 - Manual Release: Optional
- 2 Controls:
 - Controller: Hand
 - Controller Mount: Pedestal
 - Controller Hose: 6 Feet
 - Controller Cable: 12 Feet
- 3 Color:
 - Lift: Herkules Safety Orange
 - Scissors: Herkules Safety White
 - Controls: Herkules Safety Orange
- 4 Safety Features:
 - Flow Control Valve: Qty - 1 Included
 - Maintenance Stop: Qty - 1 Included
 - Safety Skirting: Optional
- 5 Cycle Speed:
 - Average Speed: Customer Defined
 - Speed Up: Customer Defined
 - Speed Down: Customer Defined
- 6 Electrical:
 - E-Stop: Included
 - Breaker Box: Optional
 - Motor Connector Plugs: Optional
 - Field Wiring: Optional
 - Limit Switches: Optional

Notes

- 1 Various options may be available which deviate from our standard lift specifications. On standard LSH lifts, optional accessories are not included. Please reference the options tab for each lift type on our webpage, and contact our sales staff.
- 2 Safety below skirting option must be purchased to meet ANSI and OSHA standards.
- 3 Surface finishes are either powder coat or low-VOC quick-dry two-stage spray-on primer coat and hard enamel top coat.